

Modeling and Simulation for Qualification of Additive Manufacturing

Albert C. To, Ph.D.

William Kepler Whiteford Professor

with contributions from Qian Chen, Hai Tran, Wen Dong, Seth Strayer, Dr. Florian Dugast, Dr. Alaa Olleak, Dr. Lin Cheng, Dr. Xuan Liang, Dr. Santanu Paul

Ansys Additive Manufacturing Research Laboratory

Department of Mechanical Engineering and Materials Science

University of Pittsburgh

GIF AMME Workshop on Advanced Manufacturing

November 8, 2021

Ansys Additive Manufacturing Research Lab (AMRL)

Optomec LENS 450



EOS M290 DMLS



- Established in 2015
- 2,000 sq ft lab space






Mitsubishi EDM
MV2400-S Wire EDM



ExOne Innovent




Build Failures - Laser Powder Bed Fusion




Modified Inherent Strain Method

Detailed model

- meso-scale (~0.1mm)
- sequentially coupled thermomechanical analysis




Extract inherent strains
(element by element)




$$\varepsilon^{In} = \varepsilon_{t_i}^{Plastic} + (\varepsilon_{t_i}^{Elastic} - \varepsilon_{t_s}^{Elastic})$$

Inherent strain model


- macro-scale (~100mm)
- Quasi-static mechanical analysis




Apply inherent strains
(layer-by-layer)



After cutting



Experimental Measurement




FEA Simulation







➤ Reduce error in deformation from 40% to 10% compared to original inherent strain model

Q. Chen, A. C. To, et al., "An inherent strain based multiscale modeling framework for simulating part-scale residual deformation for direct metal laser sintering," *Additive Manufacturing*, vol. 28, 406-418, 2019.

X. Liang, A. C. To, et al., "Modified inherent strain method for fast prediction of residual deformation in direct metal laser sintered components," *Computational Mechanics*, vol. 64, 1719-1733, 2019.



Modified Inherent Strain Method




W. Dong, A. C. To, et al "A new procedure of implementing modified inherent strain model for improving prediction accuracy of both residual stress and deformation in laser powder bed fusion parts", *Additive Manufacturing*, in press.

* T_{in} and T_{st} are material temperatures at the intermediate and steady state, respectively
 * N is the number of total layers in the FE model


Bearing Bracket Support (Re)-Design

- Combine global-local analysis, J-integral, and modified inherent strain method to predict interfacial cracking between solid component and support structure





Build Orientation Optimization

- Combine particle swarm optimization and modified inherent strain method to efficiently optimize build orientation for residual stress



Optimal Orientation




- **Reduce maximum residual stress by 40-50%**


No cracking!

Support Structure Optimization

- Combine modified inherent strain method and topology optimization to design support structure



Un-optimized support



Optimized support










L. Cheng, A. C. To, et al., "On utilizing topology optimization to design support structure to prevent stress induced build failure in laser powder bed fusion," *Additive Manufacturing*, vol. 27, 290-304, 2019.

- **Reduce maximum residual stress by 30-40%**



Fast Grain Growth Model

- Assumes epitaxial columnar dendrite is the dominant growth mechanism
- Each epitaxial columnar dendrite is modeled by a line segment
- Each dendrite is grown according to the local thermal gradient





S. Paul, A. C. To, et al., "Discrete Dendrite Dynamics Model for Epitaxial Columnar Grain Growth in Metal Additive Manufacturing with Application to Inconel," *Additive Manufacturing*, vol. 36, 101611, 2020.

Melt Pool Variation and Defect Formation




Pre-deposition temperature profile along building height


Melt Pool and Defect Prediction




Time = 0.000700



- Mesoscale computational fluid dynamics to model the heat transfer and fluid flow
- Predict the melt pool morphology and anticipated defects





Melt pool geometry




Keyhole pore generation

Effect of Preheating Temperature


Keyhole regime ($P = 250 \text{ W}$ and $V = 0.5 \text{ m/s}$)



Preheating temperature: 100 °C



Preheating temperature: 300 °C




Preheating temperature: 500 °C

Q. Chen, A. C. To, et al.
“Elucidating the effect of preheating temperature on melt pool morphology variation in Inconel 718 laser powder bed fusion via simulation and experiment,” *Additive Manufacturing*, vol. 37, 101642, 2021


Keyhole Pore Generation

For melt pool in keyhole regime ($P = 250 \text{ W}$, $V = 0.5 \text{ m/s}$):

- Increasing the preheating temperature leads to deep melt pool
- Probability of porosity occurrence is increased at higher preheating temperature




Preheating temperature: 100 °C



Preheating temperature: 500 °C

Q. Chen, A. C. To, et al.
“Elucidating the effect of preheating temperature on melt pool morphology variation in Inconel 718 laser powder bed fusion via simulation and experiment,” *Additive Manufacturing*, vol. 37, 101642, 2021

Process Window (P-V Map)



Cunningham *et al.*
(2016, 2017) JOM


GPU-based AM Process Simulator

Key Features:

- Based on *voxel mesh* and *matrix-free finite element formulation*
- Runs on a \$10-30k workstation but with supercomputer performance
- Handles highly complex geometry
- **300 times faster** running on 1 GPU than running on 1 CPU core



Layer-by-layer simulation of the “UTEP QTA block” on multi-GPUs



	Simulation time	Speedup
1 GPU	17h	-
2 GPU	10h 51 min	1.57
3 GPU	8h 50 min	1.92
4 GPU	7h 40 min	2.22
Actual build time	14 hours	-

Physical domain: 41x41x41 mm³ Number of nodes: 206x206x206

Element resolution in x and y direction: 200 microns


Layer thickness: 30 microns

Material properties: Ti64 (temperature dependent)

F. X. Dugast, A. C. To, et al. “Part-scale thermal process modeling for laser powder bed fusion with matrix-free method and GPU Computing,” *Additive Manufacturing*, vol. 37, 101732, 2021.



Multiscale Process Simulation

- Layerwise simulation is fast and can be used to detect “hot spots”
- Scanwise simulation is time-consuming and should be restricted to small millimeter-scale region
- Developing a global-local process simulation to simulate thermal history, melt pool geometry, and microstructure including porous defects



Challenges and Opportunities

- Predicting detailed temperature history and microstructure/property everywhere in a part
 - Phase field and cellular automaton limited to 1-mm region
 - Property prediction beyond static strength is challenging, and experimental data is limited
- Capturing melt pool variability
 - Laser diameter dependency on location
 - Spatter shadowing in laser path
 - Laser power/focus varies over time and differ between machines
- Predicting porosity in the “allowable process window” within a part
 - Porosity caused by spattering difficult to predict
- Data curation, storage, and mining
 - In-situ monitoring, ex-situ characterization, simulations
 - Many terabytes of data



Thank you